

Technical data

# HC 200i C P



**Compactors Series HC**  
Compactor with padfoot drum

**H256**

## HIGHLIGHTS

- > High compaction performance
- > Spacious driver's platform with Easy Drive operating concept
- > Hammtronic for high comfort, safety and reduced emissions
- > Customised configuration possibilities and a wide range of options
- > Digital ready

**TECHNICAL DATA HC 200i C P (H256)**

**Weights**

Operating weight with cab	kg lbs	19645 43,317
Operating weight with ROPS	kg lbs	19310 42,579
Empty weight without cab, without ROPS	kg lbs	18445 40,671
Maximum operating weight	kg lbs	20400 44,982
Axle load, front/rear	kg lbs	13560/6085 29,900/13,417
Axle load at maximum operating weight, front/rear	kg lbs	13590/6810 29,966/15,016
Static linear load, front	kg/cm lbs/in	63,36 354.8
French classification, value/class		87,68/VPM5
Wheel load per tire, rear	kg lbs	3042,5 6,709

**Machine dimensions**

Total length	mm in	6610 260.2
Total height with cab	mm in	3046 119.9
Total height with ROPS	mm in	3054 120.2
Height loading, min.	mm in	3046 119.9
Center distance	mm in	3312 130.4
Total width with cab	mm in	2474 97.4
Maximum working width	mm in	2140 84.3
Ground clearance, center	mm in	453 17.8
Curb clearance, left/right	mm in	469/469 18.5/18.5
Turning radius, inside	mm in	4278 168.4
Slope angle, front/rear	°	33,6/25,7

**Drum dimensions**

Drum width, front	mm in	2140 84.3
Drum diameter, front	mm in	1803 71.0
Drum thickness, front	mm in	35 1.4
Drum type, front		Padfoot
Height of the padfeet	mm in	112 4.4
Padfeet, quantity		140

**Tire dimensions**

Tire size, rear		TR 23.1/18-26 12 PR
-----------------	--	---------------------

**Tire dimensions**

Width over tires, rear	mm in	2140 84.3
Number of tires, rear		2

**Diesel engine**

Manufacturer		DEUTZ
Model		TCD 6.1 L6
Cylinders, quantity		6
Power ISO 14396, kW/PS/rpm		160,0/217,7/2000
Power SAE J1349, kW/HP/rpm		160,0/214,7/2000
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		DOC-DPF-SCR

**Travel drive**

Speed, infinitely variable	km/h mph	0 - 11,5 0.0 - 7.1
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	59/66

**Vibration**

Vibration frequency, front, I/II	Hz vpm	27/30 1,620/1,800
Amplitude, front, I/II	mm in	2,10/1,20 .083/.047
Centrifugal force, front, I/II	kN lbs	350/250 78,750/56,250

**Steering**

Pendulum angle +/-	°	max. 12
Steering, type		Articulated steering

**Tank capacity/filling capacity**

Fuel tank, capacity	L Gal	336 88.8
AdBlue/SCR reducing agent tank, capacity	L Gal	32 8.5

**Sound level**

Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	104

**EQUIPMENT**

12 V sockets (2-fold) | Two large exterior rear-view mirrors | 3-point articulation | Dashboard with displays, indicator lights and function keys | Easy Drive operating concept | ECO mode | Speed preselect | Hose protection on the front vehicle | Vibration-isolated driver's platform | Automatic vibration system | Traction Control, automatic | Steel scraper, for padfoot drum

**OPTIONAL EQUIPMENT**